



INSTALLATION

T47 Road TO PRAXIS M30 🖊 **THREADED BB System**

TRIPEAK Product NO. EMA-T476828-PW★







Step 1

THREADED (TWIST-LOCK)


DRIVE SIDE Cup set lock to 30Nm



Bearing Options

★ SB (Steel Bearing) / ★ CB (Ceramic Bearing) Bearing Size: 30 X 42 X 7mm (6806-2RS)


Replacement Bearing set TRIPEAK item NO. SB: EMA-HP6806-2RS / CB: EMA-JC6806-2RS



Step 2

THREADED (TWIST-LOCK)

Non-DRIVE SIDE Cup set lock to 30Nm



Tool compatible with torque wrench


for installation use.

NOTICE

- To install TRiPEAK Bottom Bracket, we strongly recommend that you have a trained bicycle mechanic at your local bike shop.
- · Do not alter this product in any way as it can cause unseen damage. Any modifications to this product will void the warranty.
- Make sure with the crankset are firmly attached to the bottom bracket. Improperly attached cranks can become detached from the BB set.
- · When cleaning the bottom bracket set, only use mild soap and water. Never spray with high-pressure water. It will cause BB cup internal water ingress and influencing the bearing rolling lifetime.
- · If you have any questions or concerns about this product Please feel free to contact us. E-mail:info@tripeakbearing.com



Installed-Width



www.tripeakbearing.com