



BOTTOM BRACKET







The BB Tool

Compatible with the universal BB tool with an O.D. 44mm, eliminating the need for various specialized tools



Twist-Fit

The Twist-Fit design accomodates press-fit BB specificied frames, making the BB installation and removal easier. Dual-sided locking enhances the precision of the spindle and avoids creaking noises, by achieving a perfect alignment between the bottom bracket and the crankset spindle.



Snug Fit

The patented plastic-steel bushing design is a big relief for Press-Fit frame BB users. It prevents wear on the frame's bottom bracket shell when the BB is pressed in. Snug Fit effectively eliminates noise and corrects bottom bracket tolerances.



G5 Ceramic Balls

The ceramic bearings of the TRiPEAK C-Series utilize G5-grade ceramic balls and are paired with precisely machined steel race, delivering excellent rotational performance for riders.



P05

The TRIPEAK S-Series features P05 precision steel ball bearings, for reassuringly high smoothness and durability. 0.005 mm for eccentricity (out of roundness) of the track in the inner race. That's precise.



G3 Ceramic Balls

G3-grade perfectly round ceramic balls create lower rotational resistance, allowing your power better to convert to speed.



NC RACE

NC Race Bearings have a Nano coating on outter & inner races, This dry film can minimize the coefficient of friction to as low as 0.03 dynamic, and 0.07 for static.The Nano Coating overcomes or reduces mechanical lubrication problems improving performance and extending service life >300%



ETERNA LV Fluid

While Supra LV is focused on pure Performance of the Pulley Wheel, Tripeak chooses a different lubricant character for the ceramic bearing Bottom Bracket: The Eterna Low Viscosity (LV) Lubricant has the characteristics to be durable reliable and keep rotation silent.



ZERO Contact Seal

A non-contact bearing seal, provides complete coverage without increasing rotational resistance, striking the optimal balance between efficiency and protection.

- NC Ceramic BB -

Jet Stream Pro NC Coated Ceramic Bearings BB introduces advanced NC Nano Coating for smoother performance and extended lifespan. With Twist-Fit installation and ZeroCreak technology, it ensures easy maintenance and eliminates noise.

Enjoy a 4-year warranty for worry-free riding!



Thread Series



BB Shell Width	BB Shell DIA.	Shimano HTII SRAM DUB ROTOR 3D+
BSA 68mm	34.8mm	3 IN 1 CORE SYSTEM
ITA 70mm	36mm	3 IN 1 CORE SYSTEM
T47-68 68mm	47mm	3 IN 1 CORE SYSTEM
T47-77 77.5mm	47mm	3 IN 1 CORE SYSTEM
T47-86 86mm	47mm	3 IN 1 CORE SYSTEM



Press fit Series



BB Shell Width	BB Shell DIA.	Shimano HTII SRAM DUB ROTOR 3D+
BB30 68mm	42mm	3 IN 1 CORE SYSTEM
PF30 68mm	46mm	3 IN 1 CORE SYSTEM
BB Right	46mm	3 IN 1 CORE SYSTEM
BB 386 86mm	46mm	3 IN 1 CORE SYSTEM















BB86 Series



BB Shell BB Shell Width DIA.	Shimano HTII 24mm	SRAM DUB 28.99mm	ROTOR 3D+
BB86 41mm			













- Threaded BB -

T47-68

BB Shell 68mm BB Shell 47mm



T47-77

BB Shell 77.5mm BB Shell 47mm DIA.



Crank Spec.	Shimano HTII SRAM DUB ROTOR 3D+CAMPY Ultre Torqte 24mm 28.99mm 30mm 25mm
G5 Ceramic Bearing	3 IN 1 CORE SYSTEM
Chrome Steel Bearing	3 IN 1 CORE SYSTEM
Cup only	

T47-86

BB Shell 86mm BB Shell 47mm



Crank Spec.	Shimano HTII SRAM DUB ROTOR 3D+CAMPY Ultre Torqte 24mm 28.99mm 30mm 25mm	÷
G5 Ceramic Bearing	3 IN 1 CORE SYSTEM	_
Chrome Steel Bearing	3 IN 1 CORE SYSTEM	-
Cup only		-



- Threaded BB -

Cup only



Crank Spec.	CAMPY Ultre T Shimano HTII SRAM DUB ROTOR 3D+ 24mm 28.99mm 30mm	Forqte ROTOR TT 24mm
G5 Ceramic Bearing	3 IN 1 CORE SYSTEM	
Chrome Steel Bearing	3 IN 1 CORE SYSTEM	



BB Shell Width 70mm BB Shell 36mm



Crank Spec.	Shimano HTII	SRAM DUB 28.99mm		PY Ultre 2 25mm	Torqte ROTOR TT 24mm
G5 Ceramic Bearing		ORE SYS	STEM	 	
Chrome Steel Bearing	3 IN 1 C	ORE SYS	STEM	 	
Cup only					



without



BB Shell 68/73mm BB Shell 34.8mm







- Twist Fit BB -



BB30A

BB Shell Width 68/73mm BB Shell DIA. 42mm



Crank Spec.	Shimano HTII SRAI 24mm 28.9	M DUB ROTOR 99mm 30mn	3D+ CAMPY	' Ultre Torqte 25mm
		l I	I I	
G5 Ceramic Bearing			 	
			<u>-</u>	
Chrome Steel Bearing			 	
Cup only		-	'	

PF30

BB Shell 68mm BB Shell 46mm





PF30A

BB Shell 73mm BB Shell 46mm



Crank Spec.	Shimano HTII 24mm	SRAM DUB	ROTOR 3D+ 30mm	CAMP	/ Ultre Torqte 25mm
G5 Ceramic Bearing		CORE SYS	STEM	 	
Chrome Steel Bearing	3 IN 1 0	CORE SYS	STEM	 	
Cup only		 		 	

- Twist Fit BB -



BB386

BB Shell 86.5mm BB Shell 46mm



Shimano HTII SRAM DUB ROTOR 3D+ CAMPY Ultre Torqte 28.99mm 30mm 25mm

G5 Ceramic Bearing


Chrome Steel Bearing

Cup only

BB65

BB Shell 63mm BB Shell 65mm





BB86/92	BB Shell 8	6/92mm BB Sh	nell 41mm
Model Shimar	no HTII SRAM DUB mm 28.99mm		
G5 Ceramic Bearing			
Chrome Steel Bearing			
Cup only			



- Press Fit BB -

PF386

BB Shell 86mm BB Shell 46mm



Crank Spec.	Shimano HTII SRAM DUB ROTOR 3D+
G5 Ceramic Bearing	3 IN 1 CORE SYSTEM
Chrome Steel Bearing	3 IN 1 CORE SYSTEM

BB86

BB Shell 86/92mm BB Shell 41mm



Shimano HTII SRAM DUB ROTOR 3D+
24mm 28.99mm 30mm

3 IN 1 CORE SYSTEM

Bearing

3 IN 1 CORE SYSTEM

3 IN 1 CORE SYSTEM

without

BB90

BB Shell 90mm BB Shell 37mm



Crank Spec.	Shimano HTII 24mm
G5 Ceramic Bearing	
Chrome Steel	



TEL:+886-4-2463-6319

FAX:+886-4-2463-6382

WEB:https://tripeakbearing.com/

